

## 51-V SERIES VERTICAL SANDER & POLISHER



The 51-V is a powerful yet compact vertical sander & polisher. A smooth running pneumatic motor provides vibration free operation. It is ideal for finishing work on flat or contour surfaces.

### Features:

- Planetary gearing provides smooth operation and long life.
- Removeable side handle.
- Lightweight high-alloy aluminum housing, heat-treated for long service.
- Internal muffler built into the motor housing assures a quiet operating tool without loss of power.
- Hardened steel motor parts.
- Common motor parts with 51-H Series

Model	Throttle Type	Speed	Weight	SPECIFICATIONS		Rated Power	Inlet Size	Hose Size	Working Air Consumption
				Height to Bottom of Flange	Spindle Type				
51-VL	Lever	4000 rpm	6 lbs. 2.72 kg	5-5/8" 142.9mm	5/8-11 X 1-1/8" Long	1.5 H.P. 1.13 Kw	3/8" N.P.T	3/8"	35 cfm

## 56-V & 560-V SERIES VERTICAL GRINDERS & SANDERS



### Features:

- Corrosion resistant stainless steel governor keeps the tool at a steady R.P.M. while maintaining maximum power.
- Lightweight high-alloy aluminum housing, heat-treated for long service.
- 560-V Series has a built-in internal seal that protects the vital components in extreme dust and dirt.
- Two position "dead" handle adjusts to 90' or 120' for best control.
- Common motor parts with 56-H Series reduces spare parts inventory. • Each tool is available with a 7" or 9" guard or a 6" cup wheel guard.

SPECIFICATIONS									
Model	Throttle Type	Speed	Weight	Height to Bottom of Flange	Spindle Type	Rated Power	Inlet Size	Hose Size	Working Air Consumption
56-VL	Lever Throttle	4500 to 8000 rpm	7 lbs., 5oz.	5-1/2" - 140mm	5/8-11	3 2.25 Kw	1/2" N.P.T	1/2"	45 cfm
560-VL									
56-VS	Lockout Lever Throttle	(6000 rpm is standard)	3.3 kg	5-1/2" - 140mm	5/8-11	3 2.25 Kw	1/2" N.P.T	1/2"	45 cfm
560-VS									

Recommended working air pressure: 90 p.s.i.

Standard Equipment: Your choice of Guard, 1 - 2" Wheel Flange Wrench, 1 - Spindle Nut, 1 - Screen Bushing, 1 - type 27 wheel retainer lock.

Extra Cost Equipment

## 65-V & 660-V SERIES VERTICAL GRINDERS



### Features:

- Corrosion resistant stainless steel governor keeps the tool at a steady R.P.M. while maintaining maximum power.
- Lightweight high-alloy aluminum housing, heat-treated for long service.
- Slip-fit motor design assures simple maintenance.
- Two position "dead" handle adjusts to 90' or 120' for best control.
- Common motor parts with 65-H Series reduces spare parts inventory.

SPECIFICATIONS									
Model	Throttle Type	Speed	Weight	Height to Bottom of Flange	Spindle Type	Rated Power	Inlet Size	Hose Size	Working Air Consumption
65-VL	Lever Throttle	4000 to 8000 rpm	9/lbs. 4.3 kg	67-7/8" 164mm	5/8-11	4 H. P. 3.0 Kw	1/2 N.P.T.	1/2"	50 cfm
660-VL									
65-VS	Lockout Lever Throttle	(6000 rpm is standard)	9/lbs. 4.3 kg	67-7/8" 164mm	5/8-11	4 H. P. 3.0 Kw	1/2 N.P.T.	1/2"	50 cfm
660-VS									

### HEAVY DUTY VERTICAL GRINDERS

The 65-V is a powerful vertical grinder that will handle the heaviest metal removal and finishing work. It is ideal for use with depressed center grinding wheels, wire brushes, and cup grinding wheels. The 660-V Series is identical